



Scotchkote™ Electrical Coating

Data Sheet

January 2008

Product Description	3M™ Scotchkote™ Electrical Coating is designed as a fast-drying sealant and bonding agent intended for use on joints wrapped with plastic electrical tape.
----------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------

Product Features	<ul style="list-style-type: none">- Compatible with Scotch® Vinyl Electrical Tapes- Fast drying- Flexible when dry- Self-contained applicator- No waste if container resealed after use
-------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Applications	Scotchkote Electrical Coating is intended for use as an outer seal on vinyl tape applications which are subjected to excessive amounts of oil. It is designed to improve the weather resistance of the taped joint of splice. It is suitable for direct burial, direct water immersion or above ground applications. Contact with potable water is not recommended.
---------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Precautionary and first aid information for this product may be found in its Material Safety Data Sheet and on the product container.

Application Techniques	After taping splices with Scotch Vinyl Electrical Tape, apply Scotchkote Electrical Coating evenly over splice, extending a short distance onto the cable insulation. Be sure the surface is clean, dry and free from oil or grease before electrical coating is applied.
-------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

NOTE: Technical information provided consists of typical product data and should not be used for specification purposes. Unless otherwise noted, all tests are performed at room temperature.

Typical Physical Properties

Tack Free Time 72°F/22°C	15 minutes
------------------------------------	------------

Adhesion to:	
Wood	Good
Metal	Good
Rubber	Good
Plastic	Good

Typical Electrical Properties

Dielectric Strength	
Dry	450 volts/mil
24 hrs. in H ₂ O	200 volts/mil

Typical Chemical Properties	Solvent	Acetone, Methyl ethyl Ketone, toluene
	Solids (25%)	Synthetic rubber & resin
	Flash Point	0°F/-18°C (closed cup)
<hr/>		
Availability	3M™ Scotchkote™ Electrical Coating is available in a 4-oz. or 16-oz. can size with 10 cans per case, and may be purchased from your local electrical distributor.	

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability:

This product will be free from defects in material and manufacture for a period of two (2) years from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

3M, Scotchkote and Scotch are trademarks of 3M Company.

3M
Electrical Markets Division
6801 River Place Blvd.
Austin, TX 78726-9000
800 245 3573
FAX 800 245 0329

Please recycle. Printed in U.S.A.
© 3M 2008 All rights reserved.
78-8131-7577-1_A