

Material Safety Data Sheet This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200



WHMIS Class E: Corrosive liquid. PRODUCT IS CONTROLLED UNDER PCP. WHMIS CLASS D-1: Material causing immediate and serious toxic

HCS CLASS: Corrosive liquid.

WHMIS (Pictograms)

WHMIS (Classification)

HCS

Section 1. Chemical Product and Company Identification			
Product Name/ Trade name	Stix	Code	76
Synonym	Toilet Bowl/Porcelain/Shower Tile Cleaner	CAS#	Not applicable.
Chemical Family	Not available.	Validation Date	3/20/2004
Chemical Formula	Not applicable.	Print Date	3/27/2004
Manufacturer/ Supplier	Betco Corporation 1001 Brown Avenue Toledo, Ohio 43607 (419) 241-2156	In Case of Ch Emergency	emtrec (800) 424-9300
TSCA	TSCA Inventory: All components listed or are exempt from listing.		
DSL/ NDSL	All components listed unless noted elsewhere on this MSDS	P	rotective Clothing

Section 2. Composition and Information on Ingredients				
Name	CAS#	% by Weight	Exposure Limits	LC ₅₀ /LD ₅₀
1) Phosphoric Acid	7664-38-2	20	TWA: 1 (mg/m³) TWA: 1 (mg/m³) from OSHA (PEL) [United States] STEL: 3 (ppm)	Not available.
2) Quaternary Ammonium Chloride	68424-85-1	0.05	Not available.	Not available.

Section 3. Hazards Identification		
Potential Acute Health Effect	s Corrosive to skin and eyes on contact. Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Severe over-exposure can result in death.	
Potential Chronic Health Effects	Prolonged exposure may result in skin burns and ulcerations. Severe over-exposure can produce lung damage, choking, unconsciousness or death.	
Carcinogenic Effects	Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.	

Section 4. First	t Aid Measures
Eye Contact	Hold eye open and rinse slowly and thoroughly with water for 15 to 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor immediately for treatment advice.
Skin Contact	Remove contaminated clothing and shoes. Rinse skin with plenty of water for 15 to 20 minutes. Call a poison control center or doctor for further treatment advice.
Inhalation	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration., preferably mouth to mouth if possible. Call a poison control center or doctor for further treatment advice.

Ingestion

Call a poison control center immediately for treatment advice. Have person sip a glass of water if able to swallow. Do NOT induce vomiting unless instructed to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

Section 5. Fire Figh	Section 5. Fire Fighting Measures	
Products of Combustion	Not available.	
Fire Fighting Media and Instructions	N/A	
Special Remarks on Fire Hazards	N/A	
Special Remarks on Explosion Hazards	N/A	

Section 6. Accidental Release Measures		
Small Spill and Leak	Chemical anti-splash goggles.	
Large Spill and Leak	Absorb with an inert material and put the spilled material in an appropriate waste disposal.	
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.	

Section 7. Hand	Section 7. Handling and Storage		
Precautions	Keep locked up. Keep container dry. Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk, evaporate the residue under a fume hood. Ground all equipment containing material. DO NOT ingest. Do not breathe gas, fumes, vapor or spray. Never add water to this product. Wear suitable protective clothing. If ingested, seek medical advice immediately and show the container or the label.		
Incompatibility	Strong alkalis and oxidizers, reactive metals.		
Storage	Corrosive materials should be stored in a separate safety storage cabinet or room. Keep out of the reach of children. Not for use or storage in or around the home.		

Section 8. Exposure (Controls/Personal Protection
Engineering Controls	Good general ventilation should be sufficient to control airborne levels.
Personal Protection Eyes	Splash goggles.
Body	
Respiratory	Not applicable.
Hands	Gloves (impervious).
Protective Clothing (Pictograms)	
	Phosphoric Acid TWA: 1 (mg/m³) TWA: 1 (mg/m³) from OSHA (PEL) STEL: 3 (mg/m³)
	Consult local authorities for acceptable exposure limits.

Section 9. Physical and Chemical Properties			
Physical State and Appearance	Liquid.	Odor	Pleasant. (Slight.)
Molecular Weight	Not applicable.	Taste	Not available.
pH	1.5 to 2 [Acidic.]	Color	Clear Pink (Light.)
Boiling/Condensation Point	88°C (190.4°F)		
Melting/Freezing Point	Not available.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Specific Gravity	1.12 (Water = 1)		
Vapor Pressure	<20 mm of Hg (@ 20°C)		
Vapor Density	>1 (Air = 1)		
Volatility	Not available.		
voc	Not available.		
Evaporation Rate	<1 compared to Water		
Dispersion Properties	See solubility in water.		
Solubility	Easily soluble in cold water.		
The Product is:	May be combustible at high temperature.		
Auto-ignition Temperature	Not available.		
Flash Points	Not available.		
Flammable Limits	Not available.		
Fire Hazards in Presence of Various Substances	No specific information is available in our opresence of various materials.	latabase	regarding the flammability of this product in
Explosion Hazards in Presence of Various Substances	Not applicable		

Section 10. Stability and Reactivity Data	
Stability	The product is stable.
Incompatibility with Various Substances	Strong alkalis and oxidizers, reactive metals.
Hazardous Decomposition Products	Will not occur.

Section 11. Toxicological Information		
Routes of Entry	Absorbed through skin. Eye contact. Inhalation. Ingestion.	
Toxicity to Animals	Acute oral toxicity (LD50): 4610 mg/kg [Rat]. (Nonionic Surfactant).	
Acute Effects on Humans		
Eyes	Severe eye irritant. Liquid or mist may burn or injure the eyes.	
Skin	Severe skin irritant. Prolonged or repeated contact can cause chemical burns or dermatitis.	
Inhalation	May be irritating to mucous membranes of the nose, throat, and lungs.	
Ingestion	May be irritating to the mouth and throat. Large doses can cause nausea and vomiting.	
Chronic Effects on Humans	Prolonged exposure may result in skin burns and ulcerations. Severe over-exposure can produce lung damage, choking, unconsciousness or death.	
Special Remarks on Toxicity to Animals	No additional remark.	
Special Remarks on Chronic Effects on Humans	No additional remark.	

Section 12. Ecologic	Section 12. Ecological Information		
Ecotoxicity	Not available.		
BOD5 and COD	Not available.		
Products of Biodegradation	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.		
Toxicity of the Products of Biodegradation	Not available.		
Special Remarks on the Products of Biodegradation	No additional remark.		

Section 13. Disposal Considerations				
Waste Information	Waste must be disposed of in accordance with federal, state and local environmental control regulations.			
Waste Stream	Not available.			

Section 14. Transport Information

DOT (U.S.A) (Pictograms)



TDG Classification Class 8: Corrosive material



PIN UN, Proper Shipping Name, PG

1760 Corrosive liquid n.o.s. PG II

Maritime Transportation Not available.

Special Provisions for Transport

Not available.

Section 15. Other Regulatory Information and Pictograms						
WHMIS (Classification)		WHMIS Class E: Corrosive liquid. PRODUCT IS CONTROLLED UNDER PCP. WHMIS CLASS D-1: Material causing immediate and serious toxic effects.				
Regulatory Lists	No products were found.					
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).					
Other Classifications	HCS CLASS: Corrosive liquid.					
	USA Regulatory Lists	California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (female) which would require a warning under the statute: Ethylene Oxide <1 ppm California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Ethylene Oxide <1 ppm				
		Massachusetts RTK: Ethylene Oxide				
		SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Phosphoric Acid SARA 313 toxic chemical notification and release reporting: Phosphoric Acid				
	DSD (EEC)	R35- Causes severe burns.				
	International Regulations Lists	No products were found.				
		National Fire Protection Association (U.S.A.) Vide only a quick reference for hazard information. The ENTIRE ds, First Aid measures, and PPE associated with this product. Flammability Flammability Specific Hazard				

Section 16. Other Information					
Validated by CRushton on 3/20/2004.		Verified by CRushton.			
		Printed 3/27/2004.			
Information Contact	Betco Corporation				
	1001 Brown Avenue Toledo, Ohio 43607				
	(419) 241-2156				
Notice to Reader					
To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.					

Validated on 3/20/2004.	Stix	Page: 5/5
-------------------------	------	-----------

Continued on Next Page