MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTRIBUTOR'S INFORMATION							
NFPA Rating: Health-1;		MIS Rating: Health-1; Flammability-3; Reactivity-0; Personal Protection-B					
Manufactured For: WAXIE Sanitary Supply		DOT Hazard Classification: ORM-D					
Address:			Identity (trade name as used on label):				
Address:			,				
Address. Sail Diego, CA 92 193-1030		Spring Mint Waxie Time Metered Air Freshener					
Phone: 1-800-995-4466			MSDS Number: A06615 (metered) Revision-2				
Emergency Response Number: 1-800-255-3924			Date Prepared: 08/30/05 Prepared By: IB				
NOTICE: JUDGMENT BASED ON INDIRECT TEST DATA			Information Calls: (770)422-2071				
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION							
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES			CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)			07.10 1.10.11.20.	III LIST	(ppm)	TLV (ppm)	Ref. Source **
ACETONE			67-64-1	No	1000	750	d
ISOBUTANE / PROPANE BLEND			75-28-5	No	800	800	d
			74-98-6	No	1000	1000	d
			74 00 0	110	1000	1000	<u> </u>
A PORTION A PUNCION AND A PERSON AND A PERSO							
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS							
Boiling Point: N/A	pecific Gravity (H2O=1): Concentrate Only = < 1						
			Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A				
			Evaporation Rate (= 1): N/E				
Solubility in Water: Soluble Water Reactive: No							
Appearance and Odor: Clear liquid with fragrance. Dispenses as a dry spray bursts in metered actuation.							
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA							
	r USA FLAME PROJECTION TEST	Auto	o Ignition Temperature			s in Air by %	
(aerosols): less than 18 inches:			N/E % LEL: N/E % UEL: N/E				
NOT CATEGORIZED A							
FLASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Provide shielding for personnel. Wear							
self-contained breathing apparatus. Cool containers with water fog to prevent							
EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water. rupturing & spewing.							
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.							
SECTION 4 - REACTIVITY HAZARD DATA							
			HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR				
Incompatibility (Mat. to avoid): Alkalis, oxidizing materials, amines.			Conditions to Avoid: Open flame, welding arcs, heat.				
Hazardous Decomposition Products: CO, CO2.							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION []SKIN ABSORPTION []EYE []NOT HAZARDOUS							
ACUTE EFFECTS Vapor concentrations around 1000 ppm may cause slight transient irritation to the upper respiratory tract.							
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.							
Eye Contact: Irritation. Skin Contact: May cause slight irritation.							
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.							
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause mucous membrane irritation, overnight headache, and							
general weakness. Medical Conditions Congressly Aggregated by Evacques, May aggregate existing averable or upper receivatory conditions.							
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.							
Skin Contact: Wash with soap and water. If irritated, seek medical attention.							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.							
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.							
SECTION 6 - CONTROL AND PROTECTIVE MEASURES							
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH for organic vapor.							
Protective Gloves: Latex, if skin easily irritated. Eye Protection: Safety glasses recommended.							
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.							
Other Protective Clothing & Equipment: None							
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE							
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER.							
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.							
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F. Other Precautions & for Special Hazards: KEEP OUT OF REACH OF CHILDREN, Avoid food contamination, Avoid breathing vapors, Remove ignition sources.							
ILITHOR PROCALITIONS X/OR S	Special Hazarde: KEED () ()E DEACH ()	- (:HII I)6	TEN AVOID TOOD CONTAMINAT	IOD AVOID	Dreathing Van	are Hamava i	anition cources

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only