

MATERIAL SAFETY DATA SHEET

333 Hollenbeck St.
Rochester NY 14621
Information: 585-336-2200

Emergency Phone:
INFOTRAC: 1-800-535-5053
OUTSIDE US: 1-352-323-3500

PRODUCT NAME: SKILCRAFT ENVIROCARE TOUGH JOB CLEANER

REVISION DATE: 06/10/2003 REVISION NUMBER: 1
DATE PRINTED: 06/10/2003 PREPARED BY: EH&S DEPARTMENT

1. CHEMICAL PRODUCT

MSDS FORM NUMBER: 7223
NFPA/HMIS HAZARD CODES (minimal=0; slight=1; moderate=2; serious=3; severe=4)

Health: 1/1
Fire: 0/0
Reactivity: 0/0
Special/Protective None/B
Equipment:

2. COMPOSITION/INFORMATION ON INGREDIENTS**Non-Hazardous Components**

PRODUCT COMPOSITION CAS REGISTRATION NO.	APPROX. WEIGHT PERCENT	ACGIH TLV	ACGIH UNIT	OSHA PEL	OSHA UNIT	SARA 313 Reportable
No hazardous components. NONE	100	NA	NA	NA	NA	NA

3. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F): 212 F (C) NA
VAPOR PRESSURE: NA
VAPOR DENSITY (AIR=1): NA
SOLUBILITY IN WATER: COMPLETE
SPECIFIC GRAVITY: 1.00 - 1.04 (8.50 lb/gal)
VOC Content (%): < 6 (EPA Method 24)
VOV Content (%): NE
EVAPORATION RATE: NE
PH: 9.5 - 10.0
APPEARANCE AND ODOR: Clear. Orange Liquid. Citrus odor.

4. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (F): None (TCC) (C): NA

METHOD: TCC

SKILCRAFT ENVIROCARE TOUGH JOB CLEANER

FLAMMABLE LIMITS IN AIR - LOWER (%): NA

FLAMMABLE LIMITS IN AIR - UPPER (%): NA

EXTINGUISHING MEDIA: Water. Dry chemical. Foam.

FIRE FIGHTING PROCEDURES: Fire-fighters should wear self-contained breathing apparatus and full protective clothing when fighting chemical fires.

5. STABILITY AND REACTIVITY

STABILITY DATA: STABLE

POLYMERIZATION: Will Not Occur.

HAZARDOUS DECOMPOSITION: None

INCOMPATIBILITY (MATERIALS TO AVOID): None

CONDITIONS/HAZARDS TO AVOID: None.

6. HAZARDS IDENTIFICATION

EFFECTS FROM ACUTE EXPOSURE:

INGESTION:

May cause irritation.

SKIN CONTACT:

Prolonged contact may lead to irritation and dermatitis.

INHALATION:

Inhalation of spray mist may be irritating.

EYE CONTACT:

May cause mild eye irritation.

EFFECTS/CARCINOGENICITY:

None listed under OSHA, IARC, or NTP.

ROUTES OF ENTRY:

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation.

EMERGENCY AND FIRST AID MEASURES:

INGESTION: Contact Physician. **SKIN:** Wash with soap and water. **INHALATION:** Move person to fresh air. **EYES:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

NOTES TO PHYSICIAN: None.

SKILCRAFT ENVIROCARE TOUGH JOB CLEANER

7. HANDLING AND STORAGE

SPILL PROCEDURES:

SMALL SPILLS: Mop up all possible.

LARGE SPILLS: Dike to contain. Pick up with absorbant material. Put in suitable container for disposal. Flush remainder with water.

WASTE DISPOSAL METHODS:

Dispose in accordance with Federal, State and Local regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep out of reach of children. Avoid contact with skin and eyes. Avoid prolonged contact. Use only with adequate ventilation.

OTHER PRECAUTIONS:

No other spill procedures necessary.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE CONTROLS:

None known.

RESPIRATORY PROTECTION:

None normally required. NIOSH approved respirator if spray mist in air causes irritation.

PROTECTIVE GLOVES:

Rubber gloves.

EYE PROTECTION:

Safety Glasses.

OTHER PERSONAL PROTECTION

Appropriate protective clothing as needed to prevent skin contact.

EQUIPMENT:**VENTILATION:**

General mechanical and/or local exhaust as needed to meet exposure limits if mist in air.

Health and safety information presented on this form is generally applicable at recommended dilutions, varying only in degree. This information was compiled from current, reliable sources and is believed to be correct. As data, and/or regulations change, and conditions of use and handling are beyond our control, no warranty, express or implied, is made as to completeness or continuing accuracy of this information.

*** END OF MSDS ***