

Safety Data Sheet

SDS prepared by Steve Davis of Aardvark Clay & Supplies

GHS – United States

Section 1. Product and Company Identification

Product Name CTG06 – Speckled Grey

Synonym Ceramic Glaze - dry

Supplier/Manufacturer Aardvark Clay & Supplies
1400 East Pomona St.
Santa Ana, Ca. 92705 USA
714-541-4157 phone
714-541-2021 fax
contact@aardvarkclay.com

Emergency Phone Number 911

Product Use Pottery Manufacturing

Restrictions on use Not applicable

Section 2. Hazards Identification

GHS/Hazcom 2012 Labels	GHS/Hazcom 2012 Classifications:	
	Health:	
	CARCINOGENICITY (Inhalation) - Category 1A - (quartz) (See Section 11 for carcinogen listings)	
	SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) (respiratory tract) (inhalation) - Category 1 (quartz)	
	SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) (respiratory tract) (inhalation) - Category 3 (quartz)	
	EYE IRRITANT - Category 2A (quartz)	
	SKIN IRRITANT - Category 2 (quartz)	
Signal Word:	Environmental:	Physical:
Danger	Not Hazardous	Not Hazardous

Hazard Statements:			
Health:			
H317	May cause an allergic skin irritation.	H316	Causes mild skin irritation.
H320	Causes eye irritation	H335	May cause respiratory irritation
H372	Causes damage to organs (lungs) through prolonged or repeated exposure (inhalation).	H350	May cause cancer.
Environmental:		Physical:	
Not hazardous		Not hazardous	

Precaution Statements:			
Prevention			
P272	Contaminated clothing should not be allowed out of the workplace.	P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/spray.	P270	Do not eat, drink, or smoke when using this product.
P262	Do not get into eyes, on skin, or on clothing.	P273	Avoid release to the environment.
P264	Wash hands thoroughly after handling.	P284	[In case of inadequate ventilation] wear respiratory protection.
Response			
P304+ P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	P308+ P313	If exposed or concerned: Get medical advice/attention.
P342+ P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.	P302+ P352	IF ON SKIN: Wash with plenty of soap and water.
P305+ P351+ P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.	P333+ P313	If skin irritation or a rash occurs: Get medical advice/attention.
P337+ P313	If eye irritation persists, get medical advice/attention.	P301+ P312+ P330	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth.
P363	Wash contaminated clothing before reuse.	P301+ P330+ P331	IF SWALLOWED: Rinse mouth. DO NOT induce vomiting.
P314	Get medical advice/attention if you feel unwell.		
P391	Collect Spillage.		

Safety Data Sheet

SDS prepared by Steve Davis of Aardvark Clay & Supplies

GHS – United States

Section 2. Hazards Identification

Storage			
P402	Store in a dry place.	P403	Store in a well ventilated place.
P404	Store in a closed container.	P405	Store locked up.
Disposal		P233	Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.		
Hazards not otherwise classified:		Slippery when wet.	% of ingredients with unknown acute toxicity: None known.

Section 3. Composition / Information on Ingredients

Substance/Mixture:		Mixture - A trade secret claim is made for this glaze.		
Chemical	CAS Number	Ingredients	Chemical % of Mixture	
Quartz, (Crystalline Silica) SiO ₂	CAS # 14808-60-7	Feldspar, Silica, Zircopax	<20	
Sodium-Calcium Pentaborate Octahydrate NaO ₂ .2CaO.5B ₂ O ₃ .5H ₂ O	CAS # 1319-33-1	Ulexite from Gerstley Borate	<15	
Di-Calcium Hexaborate Pentahydrate Ca ₂ B ₆ O ₁₁ .5H ₂ O	CAS # 12291-65-5	Colemanite from Gerstley Borate	<35	
Zirconium Silicate ZrO ₂ .SiO ₂	CAS# 14940-68-2	Zircopax	<15	

Section 4. First-Aid Measures

Description of first-aid Measures:	
First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical attention.
First-aid measures after inhalation	Move victim to well ventilated area. If mechanical discomfort persists, seek medical attention.
First-aid measures after skin contact	Remove contaminated clothing. Wash affected area with soap and warm water. Obtain medical attention if irritation persists.
First-aid measures after eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking, or redness persists.
First-aid measures after ingestion	Rinse mouth. Do NOT induce vomiting. Unlikely to be toxic by ingestion. If discomfort persists, seek medical attention.
Most Important Symptoms and Effects, Both Acute and Delayed:	
Symptoms/injuries	Causes damage to organs through prolonged or repeated exposure (inhalation).
Symptoms/injuries after inhalation	May cause cancer by inhalation. Dust from this product may cause irritation to the respiratory tract.
Symptoms/injuries after skin contact	Prolonged contact with large amounts of dust may cause mechanical irritation.
Symptoms/injuries after eye contact	Prolonged contact with large amounts of dust may cause mechanical irritation.
Symptoms/injuries after ingestion	If a large quantity has been ingested, intestinal blockage and/or gastrointestinal irritation may result.
Chronic symptoms	Repeated or prolonged exposure to respirable crystalline silica dust may cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss. Acute silicosis can be fatal.

If exposed or concerned, get medical advice and attention.

Section 5. Fire-Fighting Measures

 National Fire Protection Association (U.S.A.)	
Suitable extinguishing media	This product is not combustible. Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	No restrictions on extinguishing media for this mixture.
Special hazards arising from the substance or mixture	This mixture is not flammable and does not support fire
Hazardous thermal decomposition products	This mixture does not contain hazardous decomposition products.
Special protective actions for fire-fighters	Product can become slippery when wet.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment.

Section 6. Accidental Release Measures

Use of personal precautions	Avoid inhalation of dust. Wear a N-95 face mask when cleaning up glaze dust.
Emergency procedures	There are no emergency procedures required for this mixture.
Methods and Materials for containment	There are no special spill measures that apply for mixture.
Clean up procedures	For dusts, use a vacuum to clean up spillage. If appropriate, use gentle water spray to wet down and minimize dust generation. Place waste in a sealed container.

Section 7. Handling & Storage

Precautions for safe handling	Keep bags out of direct sunlight. Do not expose dry glaze to moisture until use. Do not expose liquid glaze to freezing. Use proper lifting techniques to avoid physical injury.
Recommendations on the conditions for safe storage	No special storage considerations, but keep in a dry, cool location.

Safety Data Sheet

SDS prepared by Steve Davis of Aardvark Clay & Supplies

GHS – United States

Section 8. Exposure Controls / Personal Protection

Chemical	CAS Number	Occupational Exposure Limits
Quartz,(Crystalline Silica) SiO ₂	CAS#14808-60-7	ACGIH TLV: TWA 0.025 mg/ m ³ (respirable) OSHA PEL: TWA 10 mg/m ³ / divided by the value “%SiO ₂ ” + 2 (respirable) OSHA PEL: TWA 30 mg/m ³ / divided by the value “%SiO ₂ ” + 2 (total dust) CAL OSHA PEL: TWA .05 mg/ m ³ (respirable) CAL OSHA PEL: TWA .3 mg/ m ³ (total)
Sodium-Calcium Pentaborate Octahydrate NaO ₂ CaO ₂ .5B ₂ O ₃ .5H ₂ O	CAS # 1319-33-1	ACGIH TLV: TWA 2 mg/ m ³ OSHA PEL: TWA 5 mg/m ³ (respirable) OSHA PEL: TWA 15 mg/m ³ (total) CAL OSHA PEL: TWA 5 mg/ m ³
Di-Calcium Hexaborate Pentahydrate Ca ₂ B ₆ O ₁₁ .5H ₂ O	CAS # 12291-65-5	ACGIH TLV: TWA 2 mg/ m ³ OSHA PEL: TWA 5 mg/m ³ (respirable) OSHA PEL: TWA 15 mg/m ³ (total) CAL OSHA PEL: TWA 5 mg/ m ³
Zirconium Silicate ZrO ₂ .SiO ₂	CAS# 14940-68-2	ACGIH TLV: TWA 5 mg/ m ³ (respirable) OSHA PEL: TWA 5 mg/m ³ (respirable) OSHA PEL: TWA 15 mg/m ³ (total) CAL OSHA PEL: TWA 5 mg/m ³ (respirable)

Appropriate engineering controls: When mixing dry glazes, use local exhaust ventilation or other engineering controls as required to maintain exposures below applicable occupational exposure limits (TLV).

Recommendations for personal protective measures

Local Exhaust: When mixing glazes, use sufficient local exhaust to reduce the level of respirable dust to the applicable standards set forth in Section III - ACGIH “Industrial Ventilation, A Manual of Recommended Practice,” latest edition.

Respiratory Protection: Dust is generated when working with dry glaze. To minimize exposure to dust and/or crystalline silica(quartz), the mixing of dry glaze materials should be conducted with sufficient ventilation. Respirable dust and quartz levels should be monitored regularly. Dust and quartz levels in excess of appropriate exposure limits should be reduced by feasible engineering controls, including (but not limited to) wet suppression, ventilation, and process enclosure. When such controls are not feasible, NIOSH/MSHA approved respirators must be worn in accordance with a respiratory protection program which meets OSHA requirements as set forth at 29 CFR1910.134 and ANSI Z88.2-1080 - “Practices for Respiratory Protection”.

In most cases, a disposable N-95 Particulate Respirator is sufficient.

Eye Protection: Use NIOSH/OSHA approved safety glasses with side shields. Face shields can also be used when mixing dry glaze.

Wear tight fitting dust goggles when excessively (visible) dusty conditions are present or are anticipated.

NIOSH recommends that contact lenses not be worn when working with crystalline silica dust.

Skin Protection: Use gloves and/or protective clothing if abrasion or allergic reactions are experienced.

Work/Hygienic Practices: Avoid creating and breathing dust.

Wear NIOSH/MSHA approved dust mask when working in dust conditions - (N-95).

Food, beverages, and smoking materials should NOT be in the work area.

Persons using ceramic materials should wash thoroughly before eating, drinking, smoking, or applying cosmetics.

Protective Clothing Pictograms



N-95 face mask

Section 9. Physical & Chemical Properties

Physical State	Powder
Appearance	Tinted Powder
Odor	None
Odor Threshold	Not Applicable
pH	6 – 8
Solubility in Water	None
Melting Point	> 1300 °C (>2380°F)
Freezing Point	< 0 °C (<32°F)
Specific Gravity / Relative Density	2.35 g/cc
Evaporation Rate	No data available
Flash Point	Not Applicable
Auto-Ignition Temperature	Not Applicable
Decomposition Temperature	Not Applicable
Flammability	Not Applicable
Vapor Pressure	Not Applicable
Vapor Density	Not Applicable
Explosive Limits	Not Applicable
Viscosity	Not Applicable
Partition Coefficient: n-octanol/water	Not Applicable
Initial Boiling Point & Boiling Range	Not Applicable

Safety Data Sheet

SDS prepared by Steve Davis of Aardvark Clay & Supplies

GHS – United States

Section 10. Stability & Reactivity

Reactivity	Hazardous reactions will not occur under normal conditions.
Chemical stability	Stable at standard temperature and pressure. No stabilizers required to maintain chemical stability.
Possibility of hazardous reactions	Hazardous polymerization will not occur.
Conditions to avoid	None known
Incompatible materials	None known
Hazardous decomposition products	None known

Section 11. Toxicological Information

Routes of Exposure	Inhalation of dust, Ingestion			
Descriptions of the delayed, immediate, or chronic effects from short- and long-term exposure				
Inhalation	Inhalation of high concentrations of glaze dust may cause mechanical irritation and discomfort. Long term exposure may cause chronic effects.			
Eye Contact	Not a primary eye irritant. May cause mechanical irritation.			
Skin Contact/Irritation	Not a primary skin irritant. Not absorbed through skin. May cause dry skin.			
Sensitization	Not a sensitizer			
Ingestion	Not an ingestion hazard. If a large quantity has been ingested, intestinal blockage and/or gastrointestinal irritation may result.			
Chronic Effects				
OSHA Carcinogen	Lung cancer – Crystalline silica has been classified by OSHA as a human lung carcinogen.			
Mutagenic Effects	None Known			
Teratogenic Effects	None Known			
Developmental Toxicity	None Known			
Effects of Silicosis		Symptoms of Silicosis		
Bronchitis/Chronic Obstructive Pulmonary Disorder.		Shortness of breath; possible fever.		
Tuberculosis – Silicosis makes an individual more susceptible to TB.		Fatigue; loss of appetite.		
Scleroderma – a disease affecting skin, blood vessels, joints and skeletal muscles.		Chest pain; dry, nonproductive cough.		
Possible renal disease.		Respiratory failure, which may eventually lead to death.		
Remarks				
Carcinogenicity	Repeated or long term exposure to respirable crystalline silica dust may cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss. Acute silicosis can be fatal. Short term exposure is of little concern.			
Numerical Measures of toxicity	None Known			
OSHA, IARC, and NTP Carcinogen Classifications				
Chemical with Carcinogen Potential	CAS#	OSHA	IARC	NTP
Quartz, (Crystalline Silica) SiO2	CAS # 14808-60-7	Yes	Yes - Group 1	Yes
Zirconium Silicate Silicic acid (H4SiO4), Zirconium (4+) salt (1:1)	CAS # 10101-52-7	No	No	No
Zircopax (Zirconium Silicate) contains trace quantities (90-110pCi/g - less than or equal to 420 ppm) of naturally occurring radioactive uranium, thorium, and radium. Overexposure by inhalation to respirable dusts containing radioactive uranium, thorium, and radium may cause lung cancer.				

Section 12. Ecological Information (non-mandatory)

Ecotoxicity	None Known
Biochemical oxygen demand (BOD5)	None Known
Chemical oxygen demand (COD)	None Known
Products of Biodegradation	None Known
Toxicity of the products of Biodegradation	None Known
Bioaccumulation Potential	None Known
Potential to move from soil to groundwater	None Known
Other adverse effects	None Known

13. Disposal Considerations

Personal Protection	Refer to Section 8: "Recommendations for Personal Protective Measures" when disposing of glaze waste.
Appropriate disposal containers	Standard waste disposal containers – no specials requirements.
Appropriate disposal methods	Disposal of this product should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. In most cases, this is normal waste disposal. The generation of waste should be avoided or minimized. Dispose of non-recyclable products via a licensed waste disposal contractor. Waste packaging should be recycled. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers.
Physical and chemical properties that may affect disposal	Glaze waste should be placed in a sealed container or in a manner that reduces or eliminates the release of the product. Packaging should be recycled before disposal.
Sewage disposal	Do not dispose of into sinks or toilets. They will clog. Never dispose of this product into a sewer system.
Special precautions for landfills or incineration activities	There are no special precautions for disposal in a landfill. This product is non-combustible and is not suitable for incineration.



Safety Data Sheet

SDS prepared by Steve Davis of Aardvark Clay & Supplies

GHS – United States

Section 14. Transportation Information

Regulatory Information	UN Number	UN Proper Shipping Name	Transport Hazard Class	Packing Group Number	Bulk Transport Guidance	Special Precautions
DOT Classification	Not regulated	-	-	-	-	-
TDG Classification	Not regulated	-	-	-	-	-
ADR/RID Class	Not regulated	-	-	-	-	-
IMDG Class	Not regulated	-	-	-	-	-
IATA-DGR Class	Not regulated	-	-	-	-	-

Section 15. Regulatory Information

TSCA – Toxic Substances Control Act - EPA	Quartz and other chemicals are listed in the TSCA Chemical Substance Inventory
California Prop. 65	 WARNING: This product can expose you to chemicals including quartz which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov .
SARA/Title III (Emergency Planning & Community Right-to-Know Act)	This mixture contains no substances at or above the reporting threshold under Section 313, based on available data.

Section 16. Other Information

Definitions

OSHA means Occupational Safety & Health Administration

IARC means International Agency for Research on Cancer

NTP means National Toxicology Program

CAS means Chemical Abstract Service

ACGIH means American Conference of Governmental Industrial Hygienists

CAL-OSHA means California OSHA, most CAL-OSHA standards defer to the federal OSHA standards

OSHA means Occupational Safety & Health Administration

OSHA PEL means OSHA Permissible Exposure Limit

TWA means Time Weighted Average (average exposure on the basis of an 8h/day, 40h/week work schedule)

TLV means Threshold Limit Value - American Conference of Governmental Industrial Hygienists (ACGIH)

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.