

CUSTOMER SEE INVERSE SIDE		ATTN: MR. OF BLOGS/GROUNDS 114 LUM GREEN, KENTUCKY 42101		AL SAFETY HUNTINGTON		MECH DATE 12/28/94 PRODUCT NO 101212 INVOICE NO 668041	
SECTION I - IDENTITY		EMERGENCY TELEPHONE NO. 219/356-8100		ADDRESS (Number, Street, City, State and Zip Code) 970 East Tipton Street, Huntington, Indiana 46750			
MANUFACTURER'S NAME Huntington Laboratories, Inc.		CHEMICAL NAME AND SYNONYMS N/A		TRADE NAME AND SYNONYMS REAL-O-SOLV			
CHEMICAL FAMILY PETROLEUM DISTILLATE		FORMULA N/A					
SECTION II - HAZARDOUS INGREDIENTS							
CAS NO.	STANDARD SOLVENT	PRINCIPAL HAZARDOUS COMPONENTS		%	ACCM T/L	OSHA PEL	
8052-41-3				99	100 PPM	100 PPM	
OTHER INGREDIENTS > OR = 3%:							
NONE							
SECTION III PHYSICAL DATA							
APPEARANCE AND ODOR	COLORLESS LIQUID, SOLVENT ODOR	pH VALUE		N/A			
SPECIFIC GRAVITY (H ₂ O=1)	0.77-0.8	PERCENT VOLATILE BY VOLUME (%)	100	REACTIVITY IN WATER	NONE (ETHER = 1) > 1		
BOILING POINT (°F)	336	SOLUBILITY IN WATER	NEGL.	VAPOR DENSITY (AIR=1)	2.9		
SECTION IV - FIRE AND EXPLOSION DATA							
FLASH POINT METHOD USED	100 F, TCC	FLAMMABLE LIMITS	UNK	LOWER	2.0	AUTO IGNITION TEMP	UNK
CONT		EXTINGUISHING MEDIA	FOAM, CARBON DIOXIDE, OR DRY CHEMICAL				
UNUSUAL FIRE AND EXPLOSION HAZARDS	VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL TO IGNITION SITES AT LOCATIONS DISTANT FROM HANDLING POINT.						
SECTION V - PHYSICAL HAZARDS							
STABILITY	UNSTABLE	STABLE	X	CONDITIONS TO AVOID	ELEVATED TEMPERATURES		
INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZING AGENTS.							
HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITION MAY YIELD CARBON DIOXIDE AND CARBON MONOXIDE.							
HAZARDOUS POLYMERIZATION	MAY OCCUR	WILL OCCUR	X	CONDITIONS TO AVOID	NONE		
SECTION VI - HEALTH HAZARD DATA							
THRESHOLD (LIMIT VALUE)	SEE SEC. II	EFFECTS OF OVEREXPOSURE	1 INHALATION MAY CAUSE NASAL AND RESPIRATORY TRACT IRRITATION. SEE OTHER PRECAUTIONS.*				
2 EYES	CAUSES EYE IRRITATION.		3 SKIN MAY CAUSE SKIN IRRITATION WITH PROLONGED OR REPEATED CONTACT.				
4 INGESTION	ASPIRATION HAZARD, MAY BE HARMFUL.						
EMERGENCY AND FIRST AID PROCEDURES							
1 INHALATION MOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN.							
2 EYES IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN.							
3 SKIN FLUSH WITH PLENTY OF SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CALL A PHYSICIAN IF IRRITATION PERSISTS. WASH CLOTHING BEFORE REUSE.							
4 INGESTION DO NOT INDUCE VOMITING. GIVE VICTIM A GLASS OF WATER AND CALL A PHYSICIAN. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.							
SECTION VII - SPILL OR LEAK PROCEDURES							
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE IGNITION SOURCES. VENTILATE AREA. CONTAIN SPILL. ALL LOCAL, STATE, AND FEDERAL REGULATIONS. DO NOT CONTAMINATE FOOD/FEED/WATER.				WASTE DISPOSAL METHOD DISPOSE OF IN ACCORDANCE WITH			
SECTION VIII - SPECIAL PROTECTION INFORMATION							
RESPIRATORY PROTECTION (SPECIFY TYPE)	USE NIOSH/MSHA-APPROVED ORGANIC VAPOR MASK IF TLV EXCEEDED.			VENTILATION	LOCAL EXHAUST	SPECIAL	OTHER
PROTECTIVE CLOVES	NITRILE RUBBER.			Eye Protection	GOGGLES		
SECTION IX - SPECIAL PRECAUTIONS							
PRECAUTION TO BE TAKEN IN HANDLING AND STORAGE: STORE AWAY FROM HEAT AND FLAME. USE ONLY IN WELL- VENTILATED AREA. AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. WASH THOROUGHLY AFTER HANDLING. WET FLOORS ARE SLIPPERY. PREVENT PEDESTRIAN TRAFFIC WITH WET FLOOR SIGNS OR BARRICADES.							
OTHER PRECAUTIONS: REPEATED OR PROLONGED OVEREXPOSURE MAY LEAD TO LIVER AND KIDNEY DAMAGE. OVEREXPOSURE TO VAPORS MAY CAUSE DIZZINESS, NAUSEA, OR HEADACHE. KEEP OUT OF REACH OF CHILDREN.							

W1360-95
Huntington Labs

RECEIVED
FACILITY
Aug 1 10 01 AM '85